



WIRE	WIRE	WIRE	WIRE
1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18	19	20
21	22	23	24
25	26	27	28
29	30	31	32
33	34	35	36
37	38	39	40
41	42	43	44
45	46	47	48
49	50	51	52
53	54	55	56
57	58	59	60
61	62	63	64
65	66	67	68
69	70	71	72
73	74	75	76
77	78	79	80
81	82	83	84
85	86	87	88
89	90	91	92
93	94	95	96
97	98	99	100

NOTES:

- 1) - ALL WIRING MUST BE SIZED ACCORDING TO SHEET LETTER CODE UNLESS OTHERWISE NOTED.
- 2) - CABLE MUST BE LABELED WITH PART NUMBER.
- 3) - CABLE MUST BE BRANDED AS INDICATED.
- 4) - CO - INDICATES TWISTED WIRES FOR CAN/11939 CONNECTION.
- 5) - ALL WIRING EXCEPT CABLES SHALL BE BRANDED ACCORDING WITH WIRE NUMBER AND REVISION NUMBER.
- 6) - WIRE NUMBER SHOULD BE PRINTED EVERY 3 TO 4 INCHES ALONG WIRE LENGTH.

TITLE: Cab Load Center

DESIGNED BY: JEFF

DATE: 01/18/08

SCALE:

Page 1