



THIS DRAWING IS THE PROPERTY OF TIMBERPRO, INC. AND IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF TIMBERPRO, INC.

SHEET LETTER	WIRE SIZE	LOAD NAME
A	1/2"	300V 30A
B	1/2"	300V 30A
C	2/0"	300V 30A
D	1/2"	300V 30A
E	1/2"	300V 30A
F	1/2"	300V 30A
G	1/2"	300V 30A
H	1/2"	300V 30A
I	1/2"	300V 30A
J	1/2"	300V 30A
K	1/2"	300V 30A
L	1/2"	300V 30A
M	1/2"	300V 30A
N	1/2"	300V 30A
O	1/2"	300V 30A
P	1/2"	300V 30A
Q	1/2"	300V 30A
R	1/2"	300V 30A
S	1/2"	300V 30A
T	1/2"	300V 30A
U	1/2"	300V 30A
V	1/2"	300V 30A
W	1/2"	300V 30A
X	1/2"	300V 30A
Y	1/2"	300V 30A
Z	1/2"	300V 30A

NOTES:
 1) - ALL WIRES MUST BE SIZED ACCORDING TO SUFFIX LETTER CODE UNLESS OTHERWISE NOTED.
 2) - CABLE MUST BE LABELED WITH PART NUMBER AND REVISION LETTER.
 3) - CABLE MUST BE BUNDLED AS INDICATED.
 4) - () - INDICATES TWISTED WIRES FOR CAN/11939 COMMUNICATION.
 5) - ALL WIRES EXCEPT CABLES SHALL BE BLACK JOCKETED WITH WHITE PRINT INDICATING EACH WIRE PER NUMBER SHOWN IN THIS DRAWING. WIRE NUMBER SHOULD BE PRINTED EVERY 3 TO 4 INCHES ALONG WIRE LENGTH.