



Wire Legend

GREEN	- Ground
ORANGE	- 12 Volt
RED	- 24 Volt Battery
PURPLE	- Ignition Power
LT BLUE	- ACC Power
BLUE	- Heater/AC

LETTER	WIRE SIZE	WIRE NAME	LENGTH
A	1/2"	300-300	300
B	1/2"	300-300	300
C	1/2"	300-300	300
D	1/2"	300-300	300
E	1/2"	300-300	300
F	1/2"	300-300	300
G	1/2"	300-300	300
H	1/2"	300-300	300
I	1/2"	300-300	300
J	1/2"	300-300	300
K	1/2"	300-300	300
L	1/2"	300-300	300
M	1/2"	300-300	300
N	1/2"	300-300	300
O	1/2"	300-300	300
P	1/2"	300-300	300
Q	1/2"	300-300	300
R	1/2"	300-300	300
S	1/2"	300-300	300
T	1/2"	300-300	300
U	1/2"	300-300	300
V	1/2"	300-300	300
W	1/2"	300-300	300
X	1/2"	300-300	300
Y	1/2"	300-300	300
Z	1/2"	300-300	300

- NOTES:**
- 1) - ALL WIRES MUST BE SIZED ACCORDING TO SUFFIX LETTER CODE UNLESS OTHERWISE NOTED.
 - 2) - CABLE MUST BE LABELLED WITH PART NUMBER AND REVISION LETTER.
 - 3) - CABLE MUST BE BRANDED AS INDICATED.
 - 4) - ○ - ○ - INDICATES TWISTED WIRES FOR CAN/11939 COMMUNICATION.
 - 5) - ALL WIRES EXCEPT QUATRY SHALL BE BLACK JACKETED WITH WHITE PRINT NUMBERING DATA WITH THE NUMBER SHOWN IN THIS DRAWING. WIRE NUMBERS SHOULD BE PRINTED EVERY 3 TO 4 INCHES ALONG WIRE LENGTH.

TimberPro, INC	
SHAWANO, WISCONSIN 54166	
TITLE	Engine - Cummins OSC Tier 3
DESIGNED BY	JEFF
DATE	10/10/15
SCALE	
SHEET	Page 8
REV. NO.	
REV. DATE	