



8
7
6
5
4
3
2
1

A
B
C
D

WIRE LETTER	WIRE NO.	LOAD
A	1	12VDC INPUT
A	2	GROUND
A	3	12VDC SWITCHED OUTPUT
A	4	12VDC UNSWITCHED OUTPUT
A	5	NO CONNECTION
A	6	NO CONNECTION
A	7	NO CONNECTION
A	8	NO CONNECTION
A	9	NO CONNECTION
A	10	NO CONNECTION
A	11	NO CONNECTION
A	12	NO CONNECTION
A	13	NO CONNECTION
A	14	NO CONNECTION
A	15	NO CONNECTION
A	16	NO CONNECTION
A	17	NO CONNECTION
A	18	NO CONNECTION
A	19	NO CONNECTION
A	20	NO CONNECTION
A	21	NO CONNECTION
A	22	NO CONNECTION

NOTES:
 1) - ALL WIRES MUST BE SIZED ACCORDING TO SUFFIX LETTER CODE UNLESS
 OTHERWISE NOTED.
 2) - CABLE MUST BE LABELED WITH PART NUMBER
 AND REVISION LETTER.
 3) - CABLE MUST BE BUNDLED AS INDICATED.
 4) - CO - INDICATES TWISTED WIRES PER CAN/J1939 COMMUNICATION.
 5) - ALL WIRES EXCEPT OUTLET SHALL BE BLACK UNLESS OTHERWISE NOTED.
 PART NUMBERS SHALL BE PRINTED IN THIS DRAWING.
 PART NUMBERS SHOULD BE PRINTED EVERY 3 TO 4 INCHES ALONG
 WIRE LENGTH.

TITLE: Cab Load Center
DESIGNER: JEFF
DATE: 01/18/08
SCALE:
SHEET: TRN-VT
NO.: 1
TOTAL: 1

TimberPro, INC
 SHAWANO, WISCONSIN 54156

A
B
C
D