



THIS DRAWING IS THE PROPERTY OF THE COMPANY AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEMS WITHOUT THE WRITTEN PERMISSION OF THE COMPANY. THE COMPANY SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING CONSEQUENTIAL DAMAGES, ARISING FROM THE USE OF THIS DRAWING. THE COMPANY IS STRICTLY PROHIBITED FROM REPRODUCING OR TRANSMITTING THIS DRAWING TO ANY OTHER PARTY.

LETTER	WIRE	LOAD
A	4/0	300V
B	3/0	200V
C	2/0	150V
D	1/0	100V
E	1/2	75V
F	3/8	50V
G	1/4	30V
H	3/16	20V
I	1/8	15V
J	1/16	10V
K	1/32	5V
L	1/64	2.5V
M	1/128	1.25V
N	1/256	0.625V
O	1/512	0.3125V
P	1/1024	0.15625V

NOTES:  
1) - ALL WIRE SIZE MUST BE SIZED ACCORDING TO SPIRAX LETTER CODE UNLESS OTHERWISE NOTED.  
2) - CABLE MUST BE LABELED WITH PART NUMBER AND REVISION LETTER.  
3) - CABLE MUST BE BRIDGED AS INDICATED.  
4) - <C> - INDICATES TWISTED WIRES FOR CAN/1539 COMMUNICATION.  
5) - ALL WIRES EXCEPT GATES SHALL BE BLACK ADDED WITH WHITE PRINT INDENTIFYING EACH WIRE PER NUMBER SHOWN IN THIS DRAWING. WIRE NUMBER SHOULD BE PRINTED EVERY 3 TO 4 INCHES ALONG THE LENGTH.